



SOLITEX EXTASANA® is compatible with all pro clima adhesive tapes and sealants. Optimum weatherproofing is achieved when wind tight connections are made between SOLITEX EXTASANA® and other building materials and components. The table below provides guidance on the use of pro clima adhesive products when used to connect SOLITEX EXTASANA® with other common building materials.

		TESCON EXTORA®	TESCON EXTORA® PROFIL	TESCON EXTOSEAL®	ORCON® NAUDECK	CONTEGA® CLASSIC	KAFLEX® mono/dbo	KAFLEX® test	ROFLEX	DUPLEX	TESCON® PRIMER RP
Timber, OSB, Plywood	dirty		✓								✓
	clean	✓	✓	✓	✓						✓
Plaster board	clean	✓	✓	✓	✓						✓
Paint primers		✓	✓	✓	✓	✓				✓	✓
AEROSANA® VISCONN	dry / clean	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
PIR Polysiocanurate	on foil	✓	✓	✓	✓		✓	✓	✓		✓
	on PIR										
XPS Extruded Polystyrene	clean	✓	✓	✓	✓		✓	✓	✓		✓
EPS Expanded Polystyrene	clean	✓	✓	✓	✓		✓	✓	✓		✓
Expanding foams	dry										
Cement/Gypsum plaster	smooth	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough				✓						✓
	friable										✓
Acrylic plaster	smooth	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough				✓						✓
Steel	galvanized	✓	✓	✓	✓						✓
	bright	✓	✓	✓	✓						✓
	painted	✓	✓	✓	✓						✓
Aluminium	clean	✓	✓	✓	✓						✓
Brickwork	rough				✓						✓
	friable										✓
Dampcourse	aluminium				✓						✓
	polyethene				✓						✓
Chemical tremite barrier	blue	✓	✓	✓	✓	✓				✓	✓
	orange	✓	✓	✓	✓	✓				✓	✓
Concrete	smooth	✓	✓	✓	✓	✓	✓	✓			✓
	rough				✓						✓
Fibre cement	clean	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	friable										✓
Window Frames	aluminium	✓	✓	✓	✓	✓					✓
	PVC	✓	✓	✓	✓	✓					✓
	timber	✓	✓	✓	✓	✓					✓
Cables	flat	✓	✓	✓	✓			✓			
	round	✓	✓	✓	✓		✓				
Pipes / ductings		✓	✓	✓	✓			✓			

Notes:

- Surface should always be dry.
- TESCON® PRIMER RP is always recommended for mineralic surfaces.

23 11 2020



Your local support

1800 PRO CLIMA (776 254)

Technical: support@proclima.com.au | General: welcome@proclima.com.au

www.proclima.com.au

