

Specification Guidelines

WALL WEATHER RESISTIVE BARRIER

pro clima SOLITEX EXTASANA® (or approved equivalent) to be selected meeting the below performance criteria:

- Non-porous, monolithic membrane technology
- 180 days UV exposure
- ≥ 100 °C temperature resistance
- Class 4 Vapour Permeable (AS/NZS 4200.1)
- Compliant with AS/NZS 4200.1
- Flammability index less than 5 (AS/NZS 1530.2) and less than 1 mm thickness

pro clima SOLITEX EXTASANA® (or approved equivalent) must be installed in accordance with manufacturer's installation guidelines.

SELF-ADHESIVE WALL WEATHER RESISTIVE BARRIER

pro clima SOLITEX EXTASANA ADHERO® (or approved equivalent) to be selected, meeting the below performance criteria:

- Non-porous, monolithic membrane technology
- 180 days UV exposure
- ≥ 100 °C temperature resistance
- Compliant with AS/NZS 4200.1
- Flammability index less than 5 (AS/NZS 1530.2) and less than 1 mm thickness

pro clima SOLITEX EXTASANA ADHERO® (or approved equivalent) must be installed in accordance with manufacturer's installation guidelines.

ROOF WEATHER RESISTIVE BARRIER

pro clima SOLITEX MENTO® PLUS (or approved equivalent) to be selected meeting the below performance criteria:

- Non-porous, monolithic membrane technology
- 180 days UV exposure
- 100 °C temperature resistance
- Class 4 Vapour Permeable (AS/NZS 4200.1)
- Medium duty classification (AS/NZS 4200.1)
- Compliant with AS/NZS 4200.1
- Flammability index less than 5 (AS/NZS 1530.2) and less than 1 mm thickness

SOLITEX MENTO® PLUS (or approved equivalent) must be installed in accordance with the manufacturer's installation guidelines.

WALL WEATHER RESISTIVE BARRIER FOR TROPICAL CLIMATES (Climate Zone 1)

pro clima DA (or approved equivalent) to be selected meeting the below performance criteria:

- Non-porous, monolithic membrane technology
- 90 days UV exposure
- 100 °C temperature resistance
- Class 2 Vapour Classification (AS/NZS 4200.1)
- Compliant with AS/NZS 4200.1
- Flammability index less than 5 (AS/NZS 1530.2) and less than 1 mm thickness

pro clima DA (or approved equivalent) must be installed in accordance with manufacturer's installation guidelines.

INTELLIGENT AIR BARRIER

INTELLO® PLUS (or approved equivalent) to be selected, meeting the below performance criteria:

- Intelligent Air Barrier with humidity variable functionality
- Air control classified as (air barrier (AS/NZS 4200.1)
- Flammability index less than 5 (AS/NZS 1530.2) and less than 1 mm thickness

INTELLO® PLUS (or approved equivalent) must be installed in accordance with the manufacturer's installation guidelines.



Your local support

1800 PRO CLIMA (776 254)

Technical: support@proclima.com.au | General: welcome@proclima.com.au

www.proclima.com.au

